



Drawings not to scale  
All dimensions in mm (inches) nominal

UL approved

## SPECIFICATION

CONTACT FORM		Reversible Float
SWITCHING VOLTAGE	Max. V	240 Vac/200 Vdc
SWITCHING CURRENT	Max. A	0.5
CARRY CURRENT	Max. A	1.0
SWITCHING CAPACITY	Max. VA	50
CONTACT RESISTANCE	Max. mΩ	200
LEAD WIRE		XLPE (UL3266, AWG22)
OPERATING PRESSURE	Max. Kg/cm <sup>2</sup>	30
OPERATING TEMPERATURE	Deg. °C	-10° +120°
MATERIAL		Stainless Steel SUS304
SUITABLE SPECIFIC GRAVITY		0.55
WEIGHT	gm.	195
CLEARANCE HOLE DIA.	mm.	17

### FLOAT - Reed Switch - Stainless Steel

PART NUMBER  
**HFS50**

Rev. No.	Revision Note	Date	Signature
A	Web Site 2003	1-7-03	RG

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and details of our full design and manufacturing service. All products are supplied to our standard conditions of sale otherwise agreed in writing.