




Part Number: PDT1004 45° Smart Tilt Sensor Product Data Sheet


PICTURE






- · No mechanical parts
- · Smart signal conditioning by micro-controller
- · Short circuit, overload protection
- Thermal shutdown

✓ RoHS Compliant



DIMENSIONS



Drawings not to scale.
All dimensions in mm (inches) nominal.

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

Phone: (1) 973 777 6900

www.comus-intl.com

Fax: (1) 973 777 8405






Part Number: PDT1004 45° Smart Tilt Sensor Product Data Sheet

SPECIFICATION			
Supply Voltage	10 - 30	VDC	
Supply Current Max @ Vs = 24V	7	mA	
Off-State leak. Current Max	25	μΑ	
Load Current Max (Vs = 12V @ 25°C)	1.5	A	
Overvoltage Shutdown Max	42	V	
Switch Angle	45 ± 0.3	0	
Zero Level Change vs Temperature Delta from 25°C	±0.04° see below	°/°C	
Protection	IP67		
Housing Material	ABS		
Connection Cable	3 x 0.15mm ² LIYY		
Operation Temperature	-20+80	°C	

CURVE CHARACTERISTICS



As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.