

DETAILS

Protection against outside attack. The tactile tamper switch will trigger if the front cover is removed or if the unit is forcibly removed.

Coloured LED light shows the status of the controller.

Jumper links to select the appropriate resistor combination for various alarm panels.

Low power warning light.

Two independent outputs, Top button pair activate alarm A, side button pair activates alarm B.

Features Include		Specifications	
• 4 Button operation with timer.		 BE EN50131-2-6 Approved. 	
Slim design access.Tamper switch protection.Easily resettable with rotation of key.		• Grade 3.	
Did you know we also sell?		 Slim curved design. 	
	🕒 🚁 🤝 🧇	• Multiple cable entry points.	
Float Switches Pressure Switches Magnets Proximity Switches Switches Reed Relays		ED indicator	
Rev. No.	Revision Note	Date	Signature
1	Datasheet	16-09-15	ML
	As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.		
OUALITY MINAGEMENT 003	Phone : +44 (0)1255 862236	www.comus-intl.com	Fax: +44 (0)1255 862014
ISO 9001:2008 Certificate No. FM21080	©2015 Copyright Comus Europe Ltd, Unit 7, Rice Bridge Industrial Estate, Thorpe - Le - Soken, Essex, CO16 0HL, ENGLAND. USA: Comus International:+1 973 777 6900, Belgium: Comus Belgium BVBA: +32 (0)12 390400		